

14 by said cellular receiver, and providing outgoing cellular signals to said
15 transmitter, said incoming cellular signals and said outgoing cellular signals
16 containing data associated with said remote electrical switch and said sensor,
17 respectively,

18 a cellular link to the Internet,

19 a data center coupled to the Internet and configured for receiving said
20 data from the Internet and transmitting said data to the Internet,

21 a user interface in said data center responsive to said data from said
22 cellular transmitter and for inputting said data to said cellular receiver, and
23 providing control and monitoring of said plurality of remote electrical switches
24 and said at least one parameter from said sensor.

1 3 (new). A control system as set forth in claim 2 wherein said sensor includes
2 said switch so that status of said switch is monitored.

1 4 (new). A control system as set forth in claim 2 wherein said separate,
2 discrete system further comprises groups of subsystems, each group of said
3 groups of subsystems comprising at least one said remote electrical switch of
4 said plurality of remote electrical switches and at least one said sensor, with a
5 said cellular transmitter, a said cellular receiver and a said microprocessor
6 coupled to monitor and control an associated said group.

1 5 (new). A control system as set forth in claim 4 wherein said user interface

2 further comprises a display of controls for said remote electrical switches and
3 indications of said parameters organized so that said a said control for said
4 switch and a said parameter associated with a said group containing said
5 switch are correspondingly identified and grouped together on said display.

1 6 (new). A control system as set forth in claim 4 wherein said remote electrical
2 switch and said sensor in each said group of said groups of subsystems are
3 identical, with said microprocessor programmed to respond to a first unique
4 cellular transmission from said control center and initiate a second unique
5 cellular transmission to said control center.

1 7 (new). A control system as set forth in claim 6 wherein said first unique
2 cellular transmission energizes or wakes up said microprocessor and a
3 following cellular data transmission from said control center provides
4 instructions to said microprocessor.

1 8 (new). A control system as set forth in claim 7 wherein said first unique
2 cellular transmission is in the form of a MIN number and said following cellular
3 data transmission is in the form of a MIN number, and said instructions cause
4 a change of state of said switch.

1 9. A control system as set forth in claim 8 wherein said second unique cellular
2 transmission is in the form of an electronic serial number of said cellular

3 transmitter, said electronic serial number including information related to said
4 sensor.

1 10 (new). A control system as set forth in claim 9 wherein said separate,
2 discrete system is a railroad switchyard comprising a plurality of railroad
3 switches, each railroad switch of said plurality of railroad switches equipped
4 with a pair of heaters for melting snow and ice, with a pair of
5 energizing/deenergizing switches, each switch of said pair of
6 energizing/deenergizing switches coupled to energize and deenergize a
7 respective heater of said pair of heaters responsive to said incoming cellular
8 signals, and a pair of ON/OFF sensors, each sensor of said pair of ON/OFF
9 sensors coupled to sense an energized or deenergized state of a respective said
10 heater of said pair of heaters, each of said sensors providing an indication of
11 said energized or deenergized state of a respective said heater to said
12 microprocessor whereupon said indication is transmitted to said data center.

1 11 (new). A control system as set forth in claim 10 wherein a single said group
2 of said railroad switchyard comprises a said railroad switch, an associated said
3 pair of heaters, an associated said pair of sensors, an associated said cellular
4 transmitter and associated said cellular receiver and an associated said
5 microprocessor.

1 12 (new). A control system as set forth in claim 10 wherein said user interface

2 in said data center provides a control for energizing and deenergizing each said
3 pair of railroad heaters, either separately or together, and said parameter is an
4 indication of said energized or deenergized state of each said heater as provided
5 by a respective said sensor.

1 13 (new). A control system as set forth in claim 12 wherein said sensor
2 includes a sensor for monitoring an electrical current condition in each said
3 heater wherein current flowing in each said heater is sampled to determine an
4 overcurrent or undercurrent condition in each said heater.

1 14 (new). A system for energizing and deenergizing railroad switch heaters
2 from a remote location and providing at least an indication of an energized or
3 deenergized state of each said railroad switch heater, said system comprising:
4 an electrical switch for each said switch heater, said electrical switch
5 coupled to connect and disconnect electrical power to a respective said switch
6 heater, and responsive to an electrical CONNECT signal and an electrical
7 DISCONNECT signal to either connect or disconnect said electrical heater,
8 at least one CONNECT/DISCONNECT sensor for each said electrical
9 switch for providing at least an indication of an energized or deenergized state of
10 a respective said switch heater,
11 a cellular transmitter and a cellular receiver,
12 a microprocessor responsive to said cellular transmitter and to said
13 cellular receiver, and coupled to said electrical switch to trigger said electrical

14 switch to a connected or disconnected state responsive to received cellular
15 signals containing either a said CONNECT signal or a said DISCONNECT signal
16 from said cellular receiver.

1 15 (new). A system as set forth in claim 14 wherein said remote location
2 further comprises a computerized data center coupled to the Internet for
3 relaying said CONNECT signal or said DISCONNECT signal.

1 16 (new). A system as set forth in claim 15 wherein said data center further
2 comprises a computer system including computer monitors upon which
3 displays relating to status and operation of each said electrical switch and
4 status and operation of each said electrical heater are monitored.

1 17 (new). A system as set forth in claim 15 wherein said cellular transmitter
2 and said cellular receiver communicate via control channels of the cellular
3 system.